

**JUTE NET
FOR TRADITIONAL LIME AND/OR CLAY BASED MORTARS**



AREAS OF USE

Reinforcement for traditional clay and/or lime based mortars. Reinforces their stability and increases the cracking resistance of thick coatings (min 10 mm) of interior walls, heterogeneous substrates and in areas to be plastered that are not compatible, such as wood. For interior use only.

COMPOSITION

Hammock manufactured from vegetable jute fibres. Produced in Portugal.

EXECUTION

After the application of a coating, the jute net is applied over the still fresh coating. It is applied with a stainless steel trowel or by hand. There should be an overlap of about 10 cm at the nets' junction. After the coating has dried it is necessary to ensure that the net is correctly adhered before applying the second coat of coating. It is recommended to read the recommendations of the mortar manufacturer before applying.

PRECAUTIONS FOR USE

- Cut with scissors.
- Keep out of reach of children.
- Consult a doctor if swallowed.

DELIVERY AND STORAGE

Packaging : In rolls

Dimensions :

Roll width \approx 1m

Length of the roll \approx 50m

Roll surface \approx 50m²

Weight : 6 kg

Store in a dry place on a pallet, protected from moisture. Under these conditions, jute fabric rolls can be stored for an unlimited period.

TECHNICAL CHARACTERISTICS

Mesh size 4.0x4.2 mm (\pm 9%)

Total weight of dry fabric 114 g/m² (minimum weight)

Moisture content - 6.9

Longitudinal tensile strength - 6,2 N/mm

Transversal tensile strength - 5,8 N/mm

Thickness - 0,8 mm (indicative value)

